Empowered by Innovation

NEC

NEC MultiSync® LCD4010

- New backlight system for increased power efficiency and longer life time
- TileMatrix function for video walls (up to 5 x 5) with integrated tiling functions
- Intelligent Power Management features to reduce TCO (Total Cost of Ownership)
- Intelligent self-diagnosis features
- NaViSet™ and NaViSet™ Administrator compatible
- Video detect for signal priority setting
- 16:9 aspect ratio
- Colour temperature range up to 10.000 K

see more.

NEC Display Solutions

NEC MultiSync® LCD4010

Panel Technology	PVA TFT
Active Screen Area (w x h) [mm]	885.2 x 497.6
Screen Size [inch/cm]	40/101.6
Viewing Angle (typ.)	170° horizontal / 170° vertical (at contrast ratio 10:1)
Screen Aspect Ratio	16:9
Pixel Pitch [mm]	0.648 x 0.648
Contrast Ratio (typ.)	800:1
Brightness (typ.) [cd/m^2]	500
Response Time (typ.) [msec]	8 (t_r + t_f ; grey to grey); 16 (6 white/black; 10 black/white)
Colours [million]	16.77
Horizontal Frequency [kHz]	31.5-91.1 (analog and digital)
Vertical Frequency [Hz]	50.0-85.0
Optimum Resolution	1366 x 768 at 60 Hz
Other Resolutions	1600 x 1200; 1280 x 1024; 1280 x 768; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Analog: mini D-sub 15 pin; 5 x BNC; Digital: DVI-D
Audio Input	1 x RCA; 1 x S-Video; 2 x BNC (Composite and Component)
Audio Output	1 x BNC (Composite and RCA)
Composite Video	BNC/RCA
Component Video	BNC
Plug & Play	VESA DDC2Bi
Safety and Ergonomics	UL/C-UL or CSA; FCC Class B; TÜV GS; VCCI; CE; C-tick; PSB; CCC
Power Consumption [W]	230
Power Management	VESA DPMS
Power Requirements	100-120/220-240V; 2.6/1.1A; internal power supply
Operating Temperature [°C]	+ 5 to + 40
Operating Humidity [%]	20 to 80
VESA Mounting Interface	600 x 200 (FDM); 14 holes / 100 mm spacing
Dimensions (W x H x D) [mm]	With stand: 981.8 x 611.1 x 330.0 Without stand: 981.8 x 579.8 x 140
Bezel Width [mm]	46.6 left/right; 39.3 top/bottom
Specials	Scheduler (with RTC); Touch Panel ready; OmniColor™: sRGB Support and 6-axis Colour Control; 10bit Gamma Correction; AutoBright (Signal Input); Off-Timer; TileMatrix (5 x 5); Colour Temperature Mode; CableComp; Picture in Picture Mode; Picture over Picture Mode; Rapid Response Technology; NaViSet™ and NaViSet™Administrator compatible; OSM menu
Weight [kg]	27.5 (without stand); 29.5 (with stand)
Video ready (no tuner)	PAL/SECAM/NTSC
HDTV ready (no tuner)	1080i; 720p; 480i; 480p
Audio Functions	Optional speakers (2 x 7 W)
Remote Control	RS-232C (9 pin D-sub); Administrator compatible (DDC/CI); Remote Control IR
Shipping Content	Display, Stand; Power Cable; Remote Control (IR); CD Manual; VGA-VGA Cable; Remote Control IR
Warranty	3 years warranty including backlight

OmniColor™ NaViSet™ NaViSet™ Administrator CableComp

LCD4010-UK-05/05

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. May 2005